

IEC Standard Back-Up Fuse-Links

10 / 17.5 kV Rated Voltage Range – Back-up with Striker Size: L = 367mm

Catalog No.	Ref #	I _N (A)	D (mm)	Maximum breaking current I1 (kA)	Minimum breaking current I3 (A)	Weight (kg)
45DB175V6,3P	V1000564	6.3	56	63	30	2.1
45DB175V10P	W1000565	10	56	63	43	2.1
45DB175V16P	X1000566	16	56	63	54	2.1
45DB175V20P	Y1000567	20	56	63	73	2.1
45DB175V25P	Z1000568	25	56	63	93	2.1
45DB175V32P	A1000569	31.5	56	63	105	2.1
45DB175V40P	B1000570	40	56	63	125	2.1
45DB175V50P	C1000571	50	56	63	205	2.1
45DB175V63P	D1000572	63	56	63	280	2.1
45DB175V80P	E1000573	80	65	63	350	2.6
45DB175V100P	F1000574	100	88	63	500	3.5

Indoor fuse support: SI175V367 Outdoor fuse support: SE175V367

10 / 24 kV Rated Voltage Range – Back-up with Striker Size: L = 442mm

Catalog No.	Ref #	I _N (A)	D (mm)	Maximum breaking current I1 (kA)	Minimum breaking current I3 (A)	Weight (kg)
45DB240V1P	A1000109	1	56	63	14	2.5
45DB240V2P	B1000110	2	56	63	16	2.5
45DB240V4P	C1000111	4	56	63	23	2.5
45DB240V6,3P	S209339	6.3	56	63	30	2.5
45DB240V10P	T209340	10	56	63	43	2.5
45DB240V16P	V209341	16	56	63	54	2.5
45DB240V20P	W209342	20	56	63	73	2.5
45DB240V25P	X209343	25	56	63	93	2.5
45DB240V32P	Y209344	31.5	56	63	105	2.5
45DB240V40P	Z209345	40	56	63	125	2.5
45DB240V50P	A209346	50	56	63	205	2.5
45DB240V63P	B209347	63	56	63	280	2.5
45DB240V80P	C209348	80	65	63	310	3.1
45DB240V100P	D209349	100	78	63	430	4.2
45DB240V125P	D1000112	125	88	40	760	5.9
45DB240V160P	E1000113	160	88	31.5	900	5.9
45DB240V200P	F1000114	200	88	31.5	1050	5.9

Indoor fuse support: SI240V442 Outdoor fuse support: SE240V442

20 / 36 kV Rated Voltage Range – Back-up with Striker Size: L = 537mm

Catalog No.	Ref #	I _N (A)	D (mm)	Maximum breaking current I1 (kA)	Minimum breaking current I3 (A)	Weight (kg)
45DB360V2P	G1000115	2	56	31.5	15	2.7
45DB360V4P	H1000116	4	56	31.5	20	2.7
45DB360V6,3PD	S209362	6.3	56	31.5	20	2.7
45DB360V10PD	T209363	10	56	31.5	33	2.7
45DB360V16PD	V209364	16	56	31.5	66	2.7
45DB360V20PD	W209365	20	56	31.5	95	2.7
45DB360V25PD	X209366	25	56	31.5	110	2.7
45DB360V32PD	Y209367	31.5	65	31.5	135	3.7
45DB360V40PD	Z209368	40	65	20	200	3.7
45DB360V50PD	J1000117	50	88	20	220	6.5
45DB360V63PD	K1000118	63	88	20	280	6.5

Indoor fuse support: SI360V537 Outdoor fuse support: SE360V537